



dk	3	3,8	4,7	5,6	7,5	9,2	11	14,5	18
k	0,96	1,2	1,5	1,65	2,2	2,5	3	4	5
b min.	15	16	18	19	22	25	28	34	40
Phillips	P 0	P 1	P 1	P 1	P 2	P 2	P 3	P 4	P 4

  

Long. / d	M1,6	M2	M2,5	M3	M4	M5	M6	M8	M10
3	.	.							
4	.	.	.	.					
5	.	.	.	.	.				
6	.	.	.	.	.	.			
8	.	.	.	.	.	.	.		
10	.	.	.	.	.	.	.	.	
12	.	.	.	.	.	.	.	.	.
14	.	.	.	.	.	.	.	.	.
16	.	.	.	.	.	.	.	.	.
18		.	.	.	.	.	.	.	.
20		.	.	.	.	.	.	.	.
22			.	.	.	.	.	.	.
25				.	.	.	.	.	.
30				.	.	.	.	.	.
35				.	.	.	.	.	.
40				.	.	.	.	.	.
45				.	.	.	.	.	.
50				.	.	.	.	.	.
55				.	.	.	.	.	.
60				.	.	.	.	.	.
65				.	.	.	.	.	.
70				.	.	.	.	.	.
75				.	.	.	.	.	.
80				.	.	.	.	.	.
85				.	.	.	.	.	.
90				.	.	.	.	.	.
95				.	.	.	.	.	.
100				.	.	.	.	.	.

### VIS A METAUX

VIS TÊTE FRAISÉE PHILIPS

DIN 965 H INOX

DIN 965 / ISO 7046

Disponible également en :

- Inox A2
- Inox A4



FIXATION STANDARD . FIXATION SUR-MESURE