



dk	4,7	5,6	7,5	9,2	11	14,5	18
f	0,6	0,75	1	1,25	1,5	2	2,5
k	1,5	1,65	2,2	2,5	3	4	5
b min.	18	19	22	25	28	34	40
Phillips	P 1	P 1	P 2	P 2	P 3	P 4	P 4
Long. / d	M2,5	M3	M4	M5	M6	M8	M10
4	.	.					
5	.	.	.				
6	.	.	.	.			
8	.	.	.	.	.		
10	.	.	.	.	.	.	
12	.	.	.	.	.	.	
14	.	.	.	.	.	.	
16	.	.	.	.	.	.	
18	.	.	.	.	.	.	
20	.	.	.	.	.	.	.
22		.	.	.	.	.	.
25		.	.	.	.	.	.
28		.	.	.	.	.	.
30		.	.	.	.	.	.
35		.	.	.	.	.	.
40		.	.	.	.	.	.
45		.	.	.	.	.	.
50		.	.	.	.	.	.
55			.	.	.	.	.
60			.	.	.	.	.
65			.	.	.	.	.
70			.	.	.	.	.
75			.	.	.	.	.
80			.	.	.	.	.
85			.	.	.	.	.
90			.	.	.	.	.
95			.	.	.	.	.
100			.	.	.	.	.

VIS A METAUX

 VIS TÊTE FRAISÉE BOMBÉE
 PHILIPS

DIN 966 H INOX

DIN 966 / ISO 7047

Disponible également en :

- Inox A2
- Inox A4

